

Product Specifications

PART NUMBER: STD134
REVISION: L

Model Number	MAX. PRESS.		MAX. SPEED	HP	kW	Net Wt.	
	bar.	PSI				lbs.	kg
6AM-ARV-54	7.0	100	3,000 RPM	4.0	3.0	21	9.5
* 6AM-ARV-54A	7.0	100	3,000 RPM	4.0	3.0	21	9.5
* 6AM-ARV-54B	7.0	100	3,000 RPM	4.0	3.0	21	9.5
6AM-ARV-55	7.0	100	3,000 RPM	4.0	3.0	21	9.5
* 6AM-ARV-77	7.0	100	3,000 RPM	4.0	3.0	21	9.5

SOUND LEVEL 90 dB(A) MAX.
 NORMAL AMBIENT +1°C. - 120°C.
 RELATIVE HUMIDITY 0% - 100%
 ENVIRONMENT HAZARDOUS AMBIENT COMBUSTIBLE
GAS AND DUST +1°C TO +40°C

CONFORMS TO EUROPEAN STANDARD EN13463-1
 NON-ELECTRICAL EQUIPMENT FOR EXPLOSIVE
 ATMOSPHERES GROUP II CAT 2 (GAS & DUST),
 PROTECTED BY CONSTRUCTION
 (SURFACE TEMP. RATED 135°C).

TECHNICAL DATA SUBJECT TO CHANGE WITHOUT NOTICE.
 DIMENSIONS SHOWN ARE FOR REF. ONLY.
 * DENOTES INACTIVE UNITS

